

wherein  
characterized in that the outer and inner layers are interconnected by a common yarn system in said circumferential direction, ~~preferably comprising a polyester multifilament of about 1100 dtex.~~

5

<sup>Claim 1</sup>  
13. A device according to ~~one of the preceding claims,~~  
<sup>wherein</sup>  
~~characterized in that the inside of the inner side portion (5) is coated by a low friction coating, preferably a silicone polymer, butadiene rubber, neoprene rubber, PVC or similar polymer.~~

10

<sup>20</sup>  
14. A method for fitting a device ~~(2) according to one of the preceding claims~~ on a vehicle wheel (1), resting against a road surface, ~~in order~~ to increase the friction between

15 the wheel and the road surface during winter conditions, <sup>comprising the steps of:</sup>  
<sup>Providing a</sup>  
said device comprising a belt (3) made substantially from

textile material and intended to encircle the tread (4) of the wheel (1) and be held in place by means of flexible inner and outer side portions (5, 6) which, at least on the

20 inside of the wheel, is tensioned by means of an elastic member (7); <sup>and by fitting</sup>  
~~characterized in that the inner side portion (5) is fitted over the tread (4) of the wheel (1) to the inside of the wheel along at least two thirds of the circumference of the wheel, preferably along as much as possible of that~~  
25 part of the circumference which does not rest against the road surface, <sup>and by rotating</sup>  
~~whereupon the wheel (1) is rotated by means of the vehicle, whereby the remaining part of the inner side portion (5) moves to assume its place on the inside of the wheel (1) and pulls the belt (3) in place along the tread~~  
30 ~~(4) of the wheel.~~

5. A device according to claim 4, wherein the outer side portion is made of a netting material, the material being ~~comprising~~ a PVC coated 1100 dtex polyester multifilament material having a netting opening of 2-7 mm.

10. A device according to claim 9, wherein ~~said~~ <sup>said</sup> textile material is a woven polyamide.

13. A device according to claim 12, wherein the polyester multifilament yarn has a fineness of about 1100 ~~dtex~~ dtex.

15. A device according to claim 14, wherein the layers are made of a polyester or polyamide multifilament material.

17. A device according to claim 16, wherein the said common yarn system ~~comprises~~ is made of a polyester multifilament having a fineness of about 1100 dtex.

19. A device according to claim 18, wherein said low friction coating is silicon polymer, butadiene rubber, neoprene rubber, PVC, or a similar polymer.

09/937591

JC16 Rec'd PCT/PTO SEP 27 2001

SUBSTITUTE SPECIFICATION

09937591.092701